



AVIATION KITS

Sealant Removal Kits

Sealant Removal Kit Includes:

- SDR4A8 Drill Motor
- 90° and/or 45° Heads
- 5pc SR40 Cutters
- 5pc SR83 Cutters
- Case



There is now a faster, safer, more effective way to remove aircraft sealants with minimal effect on paint, primer or aircraft metal. The new Sioux Aircraft Sealant Removal Tool runs at 800 RPM and is designed for use with the SR Cutters. The SR cutters included in the kit are a plastic rotary cutting tool with a 1/4 - 28 threaded steel mandrel. The cutters thread directly into the output spindle on the drills and are ideal for close quarters applications. The Sioux Aircraft Sealant Removal Kits will eliminate the need to use chemical solvents, which raise health, safety and environmental concerns and are messy to clean up.

Sealant Removal Kits



Model Number	Free Speed	Tool Weight		Tool Length		Side to Center		Air Consumption		Spindle Internal Thread
	rpm	lb	kg	in	mm	in	mm	scfm	l/s	
Sealant Removal Kit with 90° & 45° Head – 0.4 hp (0.30 kW)										
SDR4A8SF-SRK	800	2.1	0.94	10.0	255	0.7	20	21	10	1/4"-28
Sealant Removal Kit with 45° Head – 0.4 hp (0.30 kW)										
SDR4A8F-SRK	800	2.0	0.92	10.3	260	0.7	20	21	10	1/4"-28
Sealant Removal Kit with 90° Head – 0.4 hp (0.30 kW)										
SDR4A8S-SRK	800	2.1	0.94	10.0	255	0.7	20	21	10	1/4"-28

General: Air Inlet Size: 1/4" NPT • Recommended Hose Size: 3/8" (10 mm) • Performance rated @ 90 psig (6.2 bar) air pressure

Standard Equipment: Parts List • Safety and Instruction Manual